

preferred air compressor



Model Reference		UNIGY PERFORMANCE DATA							
North America	International	Nominal Power		Maximum Pressure		Minimum Capacity		Maximum Capacity	
		hp	kW	psig	bar _g	cfm	m ³ /min	cfm	m ³ /min
UNI-7-115	UNI-5-8	7.5	5.5	116	8.0	17	0.48	31	0.88
UNI-7-150	UNI-5-10	7.5	5.5	150	10.3	27	0.76	27	0.76
UNI-10-115	UNI-7-8	10	7.5	116	8	17	0.48	42	1.19
UNI-10-150	UNI-7-10	10	7.5	150	10.3	27	0.76	35	0.99
UNI-15-115	UNI-11-8	15	11	116	8	17	0.48	60	1.70
UNI-15-150	UNI-11-10	15	11	150	10.3	27	0.76	53	1.50
UNI-15-210	UNI-11-14	15	11	210	14.5	30	0.85	40	1.13

Maximum capacity tested in accordance with ISO 1217 1006 Annex C

	UNIGY Dimensions							
	length		width		height		weight	
	inch	mm	inch	mm	inch	mm	lbs	kg
Baseplate unit	48.6	1235	28	710	29.3	745	550	250
80 Gal Receiver	48.6	1235	28	710	53.6	1361	792	360
120 Gal Receiver	68.6	1742	28	710	53.6	1361	880	400
272 Litre Receiver	48.6	1235	28	710	53.2	1350	777	353
500 Litre Receiver	75.2	1910	28	710	53.2	1350	891	405

80 to 120 Gal receivers manufactured to ASME VIII Class 1 - 272 to 500 Litre receivers manufactured to EN 60/604